

DECLARATION OF PERFORMANCE

Machine strength graded structural timber

Construction product

Machine strength graded structural timber which fulfills the requirements according to EN 14081-1:2005+A1:2011. For further or more detailed information on the delivered product, in addition to what is given below, see information on the packaging or in possible accompanying commercial document.

Intended use of the construction product

For load-bearing purposes in construction works designed according to Eurocode 5 (EN 1995) and for other uses where the strength and stiffness of the structure is essential.

Producer

Company: Setra Trävaror AB Nyby
 Adress: Nybyvägen 8
 743 63 Björklinge
 Sverige
 Telefon: 018 – 560 800
 E-post: jonas.lantz@setragroup.com
 Hemsida: www.setragroup.com

System of assessment and verification of constancy of performance of the construction product

System 2+.

Certification

The notified body RISE Research Institutes of Sweden (identification number 0402) has performed an initial inspection of the manufacturing plant and of the factory production control and performs continuous surveillance, assessment and evaluation of our factory production control. RISE has issued EC Certificate of Factory Production Control Nr. 0402 – CPR – SC1077-17

Declared performance

Performance for machine strength graded structural timber in conformity with the harmonized European standard EN 14081-1:2005+A1:2011 Timber structures – Strength graded structural timber with rectangular cross section – Part 1: General requirements.

| <i>Essential characteristics</i> | <i>Declared performance</i> |
|--------------------------------------|--|
| Species/species group | WPPA: spruce (<i>Picea abies</i>) and pine (<i>Pinus sylvestris</i>) |
| Growth area | NNE Europe (Northern and North Eastern Europe) |
| Range of thickness (fire resistance) | 31 -110 mm |
| Range of width (fire resistance) | 60-300 mm |
| Surface finish | Sawn |

| | |
|---------------------------------|--|
| Dry or wet graded | Dry graded |
| Grading machine | Dynagrade HC |
| Strength, stiffness and density | <i>According to EN 338: C30, C24, C18, C16</i> |
| | <u><i>According to relevant ITT-report: TR26</i></u> |
| Durability | 4 (according to EN 350-2) |
| Reaction to fire | D-s2, d0 (according to EN 14081-1, Table C.1) |
| Release of dangerous substances | No dangerous substance to be declared |

That the performance for our construction product machine strength graded structural timber is in accordance with the declared performance given above is certified:

Björklinge.....220623.....
(place and date of issue)

Setra Trävaror AB Nyby Såg

Jonas Lantz.....
(signature)

Jonas Lantz